


**MSDS - Material Safety Data Sheet****Product Name: Frosted Lifting Tape**

MSDS No.: 145L

**I. Basic Information:****Manufacturer:** SIRCHIE FINGER PRINT LABORATORIES, INC.**Address:** 100 HUNTER PLACE**City, ST Zip:** YOUNGSVILLE, NC 27596**Emergency Contact:** Chemtrec**Emergency Telephone Number:** 800-424-9300**Contact:** DON PENVEN**Information Telephone Number:** 919-554-2244**Last Update:** 07/24/2002**Chemical State:**  Liquid  Gas  Solid**Chemical Type:**  Pure  Mixture

0	Health
0	Flammability
0	Reactivity
	Pers. Protection

**II. Ingredients:** Trade Secret

CAS No.	Chemical Name	% Range	EHS	IARC	SARA	OSHA	ACGIH	Other
			NTP	SUB Z	313	PEL	TLV	Limits
65997173	Matte acetate with acrylic adhesive*							

**III. Hazardous Identification:****Hazard Category:**
 Acute
  Chronic
  Fire
  Pressure
  Reactive
**Hazardous Identification Information:**

No hazardous components.

**IV. First Aid Measures:****Route(s) of Entry:**

None

**Health Hazards (Acute and Chronic):**

This product is considered totally safe to health and environment in normal use.

**Signs and Symptoms:**

NA

**Medical Conditions Generally Aggravated by Exposure:**

NA

**Emergency and First Aid Procedures:**

NA

**Other Health Warnings:**

NA

# MSDS - Material Safety Data Sheet

## Product Name: Frosted Lifting Tape

MSDS No.: 145L

### V. Fire Fighting Measures:

Flash Point: NA

Lower Explosive Limit: NA

Upper Explosive Limit: NA

F.P. Method: NA

Fire Extinguishing Media: Non-flammable. Use water, foam, CO2, dry chemical.

#### Special Fire Fighting Procedures:

None

#### Unusual Fire and Explosion:

None

### VI. Accidental Release Measures:

#### Steps to be Taken in Case Material is Released or Spilled:

NA

### VII. Handling and Storage:

#### Precautions to be Taken:

Storage: For best conservation of the product store in original package at normal environmental conditions. Temperature range: 10-30 degrees C, relative humidity between 30-70%.

#### Other Precautions:

None

### VIII. Exposure Controls/Personal Protection:

#### Ventilation Requirements:

None required.

#### Personal Protective Equipment:

None required.

### IX. Physical and Chemical Properties:

Boiling Point: NA

Melting Point: NA

Evaporation Rate (Butyl Acetate = 1): NA

Vapor Pressure (mm Hg.): NA

Specific Gravity (H2O = 1):

Vapor Density (AIR = 1): NA

Solubility In Water: Insoluble

Appearance and Odor: Transparent/No odor

Other Information:

### X. Stability and Reactivity:

#### Stability:

Stable

#### Incompatibility (Materials to Avoid):

# *MSDS - Material Safety Data Sheet*

## *Product Name: Frosted Lifting Tape*

### *MSDS No.: 145L*

None known

### **Decomposition/By Products:**

This product is stable and cannot release toxic substances under normal conditions.

### **Hazardous Polymerization:**

Will not occur.

### ***XI. Toxicological Information:***

Non-toxic

### ***XII. Ecological Information:***

Will not harm the environment. Recycle if possible.

### ***XIII. Disposal Considerations:***

Recycle if possible. Large quantities should be incinerated in licensed waste incinerators or disposed of as a non-hazardous waste in accordance with local, state, and federal regulations.

### ***XIV. Transport Information:***

No special requirements.

### ***XV. Regulatory Information:***

Cal. Prop 65: No ingredient listed  
Clean Air Act: No ingredient listed.  
WHMIS (Canada): Not controlled, classifications: none

### ***XVI. Other Information:***

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.

Using this product under normal, properly instructed procedures should not be hazardous.