

MSDS - Material Safety Data Sheet**Product Name: Fluorescent Magnetic Latent Print Powder**

MSDS No.: FMP01

I. Basic Information:**Manufacturer:** Sirchie Finger Print Laboratories**Address:** 100 Hunter Place**City, ST Zip:** Youngsville, NC 27596**Emergency Contact:** ChemTrec**Emergency Telephone Number:** 800-424-9300**Contact:** Tech Support**Information Telephone Number:** 919-554-2244**Last Update:** 01/27/2011**Expiration Date:****Chemical State:** Liquid Gas Solid**Chemical Type:** Pure Mixture

1	Health
1	Flammability
1	Reactivity
F	Pers. Protection

II. Ingredients: Trade Secret (N/D = Not Disclosed)

CAS No.	Chemical Name	% Range	EHS		IARC		SARA 313		OSHA PEL	ACGIH TLV	Other Limits
			NTP		SUB Z						
Proprietary	Invisible Green	>32							NE	1 mg/m3	
1309371	Iron oxide	<66							5mg/m3	10mg/m3	

III. Hazardous Identification:**Hazard Category:** Acute Chronic Fire Pressure Reactive**Hazardous Identification Information:**

Respiratory tract irritant. Skin and eye irritant. May cause siderosis.

Zinc sulfide (green) contains less than 0.5% copper as part of its chemical structure.

This material is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

IV. First Aid Measures:**Route(s) of Entry:**

Inhalation, ingestion, skin, eyes

Health Hazards (Acute and Chronic):

Chronic: Siderosis, dermatitis

Signs and Symptoms:

Inhalation: Coughing, labored breathing

Ingestion: Nausea, vomiting, diarrhea, abdominal pains

Skin: Rash, redness

Medical Conditions Generally Aggravated by Exposure:

Skin, eye, respiratory diseases

MSDS - Material Safety Data Sheet

Product Name: Fluorescent Magnetic Latent Print Powder

MSDS No.: FMP01

Emergency and First Aid Procedures:

Inhalation: Remove to fresh air. If breathing becomes difficult, give oxygen (To be administered by qualified medical personnel only!) If breathing stops, perform artificial respiration. Seek medical attention.

Ingestion: If victim is conscious and alert, give large quantities of water. (Never give anything by mouth to an unconscious person!) Induce vomiting. Lower the head so that the vomit will not re-enter the mouth and throat. Seek medical attention.

Skin: Wash with soap and water. If irritation occurs, seek medical attention.

Eyes: Rinse with plenty of water for 15 minutes and seek medical attention.

Other Health Warnings:

V. Fire Fighting Measures:

Flash Point: NE

Lower Explosive Limit: NE

Upper Explosive Limit: NE

F.P. Method:

Fire Extinguishing Media: Dry chemical, sand, graphite

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion:

Can pose dust explosion hazard if dispersed in air.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Wear dust respirator, safety goggles, and rubber gloves. Sweep up and place in bag (use a dust suppressant) or vacuum up with HEPA filter equipped instrument (recommended). Avoid creating dust. Ventilate and wash spill site after collecting solid. Dispose according to local, state, and federal regulations.

VII. Handling and Storage:

Precautions to be Taken:

Keep in closed container. Avoid incompatible materials. Use only in well-ventilated areas. Avoid dust generation and accumulation. Wash thoroughly after handling.

Other Precautions:

DO NOT wear contact lenses while using this product.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Use only in well-ventilated areas.

Personal Protective Equipment:

Safety goggles, gloves, dust respirator, protective clothing

MSDS - Material Safety Data Sheet

Product Name: Fluorescent Magnetic Latent Print Powder

MSDS No.: FMP01

IX. Physical and Chemical Properties:

Boiling Point: NE

Melting Point: 2,795 F

Evaporation Rate (Butyl Acetate = 1): NE

Vapor Pressure (mm Hg.): NE

Specific Gravity (H2O = 1):

Vapor Density (AIR = 1): NE

Solubility In Water: NE

Appearance and Odor: Greyish powder; no odor

Other Information:

X. Stability and Reactivity:

Stability:

Normally stable. May be unstable at high temperatures in air.

Incompatibility (Materials to Avoid):

Pure oxygen, strong oxidizers, mineral acids

Decomposition/By Products:

Sulfur oxides, hydrogen sulfide

Hazardous Polymerization:

Will not occur.

XI. Toxicological Information:

Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On x-rays, it appears to be a benign pneumoconiosis, and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis-producing materials such as silica. The TLV is set to protect against siderosis.

XII. Ecological Information:

Prevent from entering sewers or waterways. May be toxic to some aquatic life.

XIII. Disposal Considerations:

Dispose according to local, state, and federal regulations.

XIV. Transport Information:

Keep in closed container. Avoid incompatible materials. Avoid dust generation and accumulation. Wash thoroughly after handling.

XV. Regulatory Information:

This material is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

XVI. Other Information:

Using this product under normal, properly instructed procedures should not be hazardous.

MSDS - Material Safety Data Sheet

Product Name: Fluorescent Magnetic Latent Print Powder

MSDS No.: FMP01

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.