

MSDS - Material Safety Data Sheet**Product Name: Magnetic Latent Print Powder, Silver/Black (Also covers BPMSBM9 & BPMSBM9128)**

MSDS No.: SBM9

I. Basic Information:

Manufacturer: Sirchie Finger Print Laboratories

Address: 100 Hunter Place

City, ST Zip: Youngsville, NC 27596

Emergency Contact: ChemTrec

Emergency Telephone Number: 800-424-9300

Contact: Tech Support

Information Telephone Number: 919-554-2244

Last Update: 02/02/2011

Expiration Date:

Chemical State: Liquid Gas SolidChemical Type: Pure Mixture

| | |
|---|------------------|
| 1 | Health |
| 2 | Flammability |
| 1 | Reactivity |
| F | Pers. Protection |

II. Ingredients: Trade Secret

| CAS No. | Chemical Name | % Range | EHS | | IARC | | SARA | | OSHA PEL | ACGIH TLV | Other Limits |
|---------|---------------|---------|-----|--|-------|-----|------|---------|----------|-----------|--------------|
| | | | NTP | | SUB Z | 313 | | | | | |
| 7429905 | Aluminum | 2 | | | | | | 5 mg/m3 | 5 mg/m3 | 1,094 F | |
| 1309371 | Iron oxide | 98 | | | | | | 5mg/m3 | 10mg/m3 | | |

III. Hazardous Identification:

Hazard Category:

 Acute Chronic Fire Pressure Reactive**Hazardous Identification Information:**

May be dangerous if ingested. Respiratory tract irritant. Skin irritant. Severe eye irritant.

This material is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

IV. First Aid Measures:**Route(s) of Entry:**

Inhalation, ingestion, skin, eyes

Health Hazards (Acute and Chronic):

Chronic: Siderosis

Signs and Symptoms:

Eyes: Inflammation, redness, watering, itching

Medical Conditions Generally Aggravated by Exposure:

Skin, eye, respiratory

MSDS - Material Safety Data Sheet

Product Name: Magnetic Latent Print Powder, Silver/Black (Also covers BPMSBM9 & BPMSBM9128)

MSDS No.: SBM9

Emergency and First Aid Procedures:

Inhalation: Remove to fresh air. If breathing becomes difficult, give oxygen (To be administered by qualified medical personnel only!) If breathing stops, perform artificial respiration. Keep victim warm and at rest. Seek medical attention.

Ingestion: If victim is conscious and alert, give large quantities of water or milk. (Never give anything by mouth to an unconscious person!) Induce vomiting. Lower the head so that the vomit will not re-enter the mouth and throat. Seek medical attention.

Skin: Wash with soap and water. If irritation occurs, seek medical attention.

Eyes: Rinse with plenty of water for 15 minutes. Seek medical attention. DO NOT use an eye ointment.

Convulsions: Do not restrain the victim, but do remove objects with which they might injure themselves; or, orient the victim to prevent them from striking fixed heavy objects. If the convulsions cease, turn the victim on their side or face down, so that any fluid in the mouth can drain.

Other Health Warnings:

V. Fire Fighting Measures:

Flash Point: NE

Lower Explosive Limit: 0.035

Upper Explosive Limit: NE

F.P. Method:

Fire Extinguishing Media: Dry chemical, sand, graphite--DO NOT use water

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion:

Can pose dust explosion hazard if dispersed in air. May react with water to form combustible hydrogen gas.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Wear dust respirator, safety goggles, and rubber gloves. Sweep up and place in bag or vacuum up with proper filter equipped instrument. Avoid creating dust. Ventilate and wash spill site after collecting solid. Dispose according to local, state, and federal regulations.

VII. Handling and Storage:

Precautions to be Taken:

Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources (heat, open flame, spark). Avoid incompatible materials. Ground all equipment containing material. Use only in well-ventilated areas. Avoid dust generation and accumulation. Avoid ingestion and inhalation of dust. Avoid contact with eyes. Wash thoroughly after handling.

Caution: Wear of safety goggles is recommended when handling this product.

Caution: Wear of safety goggles is recommended when handling this product.

Other Precautions:

MSDS - Material Safety Data Sheet

Product Name: Magnetic Latent Print Powder, Silver/Black (Also covers BPMSBM9 & BPMSBM9128)

MSDS No.: SBM9

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Use only in well-ventilated areas.

Personal Protective Equipment:

Safety goggles, gloves, dust respirator, protective clothing

IX. Physical and Chemical Properties:

Boiling Point: 3,733 F

Melting Point: 1,220 F

Evaporation Rate (Butyl Acetate = 1): N/A

Vapor Pressure (mm Hg.): 1

Specific Gravity (H20 = 1):

Vapor Density (AIR = 1): N/A

Solubility In Water: Insoluble

Appearance and Odor: Silver/black powder

Other Information:

X. Stability and Reactivity:

Stability:

Normally stable

Incompatibility (Materials to Avoid):

Acids, strong alkalis, strong bases, strong oxidizers, iodates, chlorinated hydrocarbons, oxides, nitrites, nitrates, carbon disulfide, chlorides, sodium peroxide + carbon dioxide, sulfur dichloride, palladium, manganese, magnesium + potassium chlorate, sodium carbonate, sulfates, diborane, water, ignition sources (heat, open flame, spark), pure oxygen

Decomposition/By Products:

Combustible hydrogen gas

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On x-rays, it appears to be a benign pneumoconiosis, and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis-producing materials such as silica. The TLV is set to protect against siderosis.

XII. Ecological Information:

Prevent from entering sewers or waterways. May be toxic to some aquatic life.

XIII. Disposal Considerations:

Dispose according to local, state, and federal regulations.

XIV. Transport Information:

MSDS - Material Safety Data Sheet

Product Name: Magnetic Latent Print Powder, Silver/Black (Also covers BPMSBM9 & BPMSBM9128)

MSDS No.: SBM9

Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources (heat, open flame, spark). Avoid incompatible materials. Ground all equipment containing material. Avoid dust generation and accumulation. Avoid ingestion and inhalation of dust. Avoid contact with eyes. Wash thoroughly after handling.

XV. Regulatory Information:

Lycopodium is hazardous by definition of OSHA Hazard Communication Standard (29 CFR 1910.1200).

This material is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

XVI. Other Information:

Using this product under normal, properly instructed procedures should not be hazardous.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.