

SECTION 1: Identification

Identification

Product form : Mixture

Product name : 202C Ninhydrin Spray, 6oz.

Product code 202C

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Latent fingerprint developer

Details of the supplier of the safety data sheet

SIRCHIE

100 Hunter Place

Youngsville, NC 27596 - USA

T 919-554-2244; 800-356-7311 - F 919-554-2266; 800-899-8181

http://www.sirchie.com

Emergency telephone number

Emergency number : 1.800.424.9300

CHEMTREC: 1.800.424.9300

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2 H225 Skin corrosion/irritation Category 2 H315 Serious eye damage/eye irritation Category 2A H319 Germ cell mutagenicity Category 1B H340 Carcinogenicity Category 1A H350 Specific target organ toxicity (single exposure) H336 Category 3 Specific target organ toxicity (repeated exposure) H373

Category 2

Full text of H statements : see section 16

Label elements 2.2.

GHS-US labeling

Hazard pictograms (GHS-US)





GHS07

GHS08

Signal word (GHS-US) : Danger

Contains : ethyl acetate; ethylbenzene

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness H340 - May cause genetic defects (Dermal, oral)

H350 - May cause cancer (Dermal, oral)

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed P260 - Do not breathe fume, mist

P264 - Wash hands, exposed skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear eye protection, protective gloves

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

07/26/2016 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use dry chemical, foam, CO2, water spray to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/container to local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the classification

: Toxicity of this product has not been fully tested.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum gases, liquefied, sweetened	(CAS No) 68476-86-8	40 - 70	Not classified
ethyl acetate	(CAS No) 141-78-6	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
xylene, mixture of isomers	(CAS No) 1330-20-7	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
ethanol	(CAS No) 64-17-5	7 - 13	Flam. Liq. 2, H225
ethylbenzene	(CAS No) 100-41-4	3 - 7	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest. Cough.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persist. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Shortness of breath.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol. Flammable liquid and vapor. May cause fire or explosion; strong oxidizer.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries. May form flammable/explosive vapor-air mixture.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

07/26/2016 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture. Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Take any precaution to avoid mixing with combustibles/..

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

 Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products

: Strong bases. Strong acids.

Incompatible materials

: Sources of ignition. Direct sunlight. Heat sources. Combustible materials.

Storage area

: Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm (Ethanol; USA; Short time value; TLV - Adopted Value)
ethyl acetate (141-78-6)		
ACGIH	ACGIH TWA (ppm)	400 ppm (Ethyl acetate; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Not applicable		
xylene, mixture of isomers (1330-20-7)		
Not applicable		

07/26/2016 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum gases, liquefied, sweetened (68476-86-8)		
Not applicable		
ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Not applicable		

8.2. Exposure controls

Personal protective equipment : Dust/aerosol mask. Gloves. Safety glasses. Avoid all unnecessary exposure. Wear fire/flame

resistant/retardant clothing.







Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless, volatile liquid.

Color : Colorless

Odor : Irritating/pungent odour Odor threshold No data available рΗ No data available Melting point No data available Freezing point No data available : No data available Boiling point Flash point No data available : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : No data available **Explosion limits** : No data available : No data available Explosive properties

Oxidizing properties : May cause fire or explosion; strong oxidizer.

Vapor pressure : No data available
Relative density : No data available
Relative vapor density at 20 °C : No data available
Solubility : Insoluble in water.

Water: Solubility in water of component(s) of the mixture :

• ethanol: Complete • ethyl acetate: 8 g/100ml (25 °C) • xylene, mixture of isomers: < 0.02

g/100ml • ethylbenzene: 0.02 g/100ml

Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

No additional information available

07/26/2016 EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7). Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition. Flammable liquid and vapor. May form flammable/explosive vapor-air mixture. May cause fire or explosion; strong oxidizer.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; 10200 mg/kg bodyweight; Rat)
LD50 dermal rabbit	> 18000 mg/kg (Rabbit; Experimental value; 24 hour cuff method; >20000 mg/kg bodyweight; Rabbit)
LC50 inhalation rat (mg/l)	70.56 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	19600 ppm/4h (Rat)
ATE US (oral)	5620.000 mg/kg body weight
ATE US (gases)	19600.000 ppmV/4h
ATE US (vapors)	70.560 mg/l/4h
ATE US (dust, mist)	70.560 mg/l/4h
xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
ATE US (oral)	3523.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	15415.000 mg/kg body weight
ATE US (gases)	4000.000 ppmV/4h
ATE US (vapors)	17.800 mg/l/4h

07/26/2016 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylbenzene (100-41-4)	
ATE US (dust, mist)	1.500 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects (Dermal, oral).
	Based on available data, the classification criteria are not met
Carcinogenicity	: May cause cancer (Dermal, oral).
ethanol (64-17-5)	
Additional information	Ethyl alcohol (200 Proof) has been shown to cause cancer in Human and Animals when ingested in volume over time. There is no link to cancer in limited exposure scenarios.
IARC group	1 - Carcinogenic to humans
xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not classifiable
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
	Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Shortness of breath.

SECTION 12: Ecological information

12.1. Toxicity

ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (LC50; US EPA; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
ethyl acetate (141-78-6)	
LC50 fish 2	230 mg/l (LC50; US EPA; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	154 mg/l (EC50; 48 h; Daphnia magna)
ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)

12.2. Persistence and degradability

202C Ninhydrin Spray, 6oz.		
Persistence and degradability	Not established.	
ethanol (64-17-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.70 g O₂/g substance	
ThOD	2.10 g O₂/g substance	
BOD (% of ThOD)	0.43	
ethyl acetate (141-78-6)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.	

07/26/2016 EN (English US) 6/10

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethyl acetate (141-78-6)	
Biochemical oxygen demand (BOD)	0.293 g O₂/g substance
Chemical oxygen demand (COD)	1.69 g O₂/g substance
ThOD	1.82 g O₂/g substance
xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O₂/g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O₂/g substance
ThOD	3.17 g O₂/g substance
BOD (% of ThOD)	45.4 (20 days)
2.3. Bioaccumulative potential	

202C Ninhydrin Spray, 6oz.		
Bioaccumulative potential	Not established.	
ethanol (64-17-5)		
BCF fish 1	1 (BCF; Other; 72 h; Cyprinus carpio; Static system; Fresh water; Read-across)	
Log Pow	-0.31 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
ethyl acetate (141-78-6)		
BCF fish 1	30 (BCF; 3 days; Leuciscus idus; Static system)	
Log Pow	0.68 (Experimental value; EPA OPPTS 830.7560; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
xylene, mixture of isomers (1330-20-7)		
BCF fish 2	7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)	
Log Pow	3.2 (Conclusion by analogy; 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
ethylbenzene (100-41-4)		
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)	

ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Mobility in soil

ethanol (64-17-5)		
Surface tension	0.022 N/m (20 °C)	
Log Koc	Koc,PCKOCWIN v1.66; 1; Read-across	
ethyl acetate (141-78-6)		
Surface tension	0.024 N/m (20 °C)	
xylene, mixture of isomers (1330-20-7)		
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.	
ethylbenzene (100-41-4)		
Surface tension	0.029 N/m	
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value	

12.5. Other adverse effects

07/26/2016 EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to ..

Additional information : Flammable vapors may accumulate in the container. Handle empty containers with care

because residual vapors are flammable. Hazardous waste due to potential risk of explosion.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

No additional information available

Air transport

UN-No. (IATA) : 195

Proper Shipping Name (IATA) : Aerosols, flammable, containing substances in division 6.1, packing group iii

Class (IATA) : 2

Subsidiary risks (IATA) : Containing substances in Division 6.1

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

07/26/2016 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

202C Ninhydrin Spray, 6oz.

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Total Go Gitato loguitations	
202C Ninhydrin Spray, 6oz.	
U.S California - Proposition 65 - Carcinogens List	Yes
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Other information : None.

Full text of H-phrases:

NFPA reactivity

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.


NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn

readily.

O - Normally stable, even under fire exposure conditions, and are not reactive with water.

NFPA specific hazard : OX - This denotes an oxidizer, a chemical which can

greatly increase the rate of combustion/fire.



07/26/2016 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below

73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : 0

G - Safety glasses, Gloves, Vapor respirator

SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.

07/26/2016 EN (English US) 10/10