

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/01/2024 Supersedes: 10/28/2020

SECTION 1: Identification

Identification

Product form : Mixture

Product name : SB201L HI-FI Latent Print Powder, Silver/Black Product code SB201L, BPP2018, BPP20116, BPP20128

Recommended use and restrictions on use

: Latent fingerprint powder Use of the substance/mixture

Supplier

SIRCHIE

100 Hunter Place

Youngsville, NC 27596 - USA

T 919-554-2244; 800-356-7311 - F 919-554-2266; 800-899-8181

http://www.sirchie.com

Emergency telephone number

: 1.800.424.9300 (USA) +1-703-527-3887 (INTL) Emergency number

CHEMTREC: 1.800.424.9300

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Not classified

GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

Other hazards which do not result in classification

Other hazards not contributing to the classification

: Epidemiological studies of workers in the Carbon Black pigment producing industries of North America and Western Europe show no significant adverse health effect due to occupational exposure to Carbon Black pigment. Early studies in the former USSR and Eastern Europe report respiratory diseases among workers exposed to Carbon Black pigment, including bronchitis, pneumonia, emphysema, and rhinitis. Such studies are of questionable validity, due to inadequate study design and methodology, lack of appropriate controls for cigarette smoking, and other confounding factors such as concurrent exposures to carbon monoxide, coal oil and petroleum vapors. Moreover, review of these studies indicates that concentrations of Carbon Black pigment are greater that current occupational exposure standards. In Monograph 65, issued in April 1996, The International Agency for Research on Cancer (IARC) re-evaluated Carbon Black pigment and concluded that: "Although one cohort study on the Carbon Black pigment production industry showed slight excesses of cancer, the totality of the epidemiology studies, both in the Carbon Black pigment industry and in some user industries, suggested that there is inadequate evidence for the carcinogenicity in humans of Black pigment.

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

Substances 3.1.

Not applicable

3.2. **Mixtures**

Name	Product identifier	%	GHS US classification
carbon black	(CAS-No.) 1333-86-4	75	Not classified
Lycopodium	(CAS-No.) 8023-70-9	12.5	Flam. Sol. 1, H228
stearic acid	(CAS-No.) 57-11-4	> 0.36	Not classified
aluminium,powder,coated,dangerous	(CAS-No.) 7429-90-5		Not classified

08/01/2024 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

and

: Based on available data, the classification criteria are not met.

symptoms
Symptoms/effects

: Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away

from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use.

Incompatible products : Strong bases. Strong acids.

08/01/2024 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SB201L HI-FI Latent Print Powder, Silver/Black		
No additional information available		
carbon black (1333-86-4)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)	3 mg/m³ (Inhalable fraction)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) (mg/m³)	3.5 mg/m³	
Lycopodium (8023-70-9)		
No additional information available		
aluminium,powder,coated,dangerous (7429-90-5)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)	1 mg/m³ (Respirable fraction)	
stearic acid (57-11-4)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)	10 mg/m³ (Inhalable fraction) 3 mg/m³ (Respirable fraction)	

8.2. Appropriate engineering controls

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

SECTION 3. I Hysical and chemica	i properties
9.1. Information on basic physical and	d chemical properties
Physical state	: Solid
Appearance	: Powders.
Color	: Black
Odor	: odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available

08/01/2024 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: Non flammable. Flammability (solid, gas) Vapor pressure : No data available Relative vapor density at 20 °C No data available : No data available Relative density Solubility : Insoluble in water. : No data available Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature : No data available Decomposition temperature : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available : No data available Oxidizing properties

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

carbon black (1333-86-4)	
LD50 oral rat	> 10000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 28 day(s))

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

08/01/2024 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SB201L HI-FI Latent Print Powder, Silver/Black	
Additional information	This product contains less than 0.1% of absorbed PAHs (polynuclear aromatic hydrocarbons). In non-absorbed form, some PAHs have been found to be carcinogens in animal studies. No correlating carcinogenic effect, however, has been observed in humans due to exposure to Carbon Black pigment. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed, for long periods of time, to very high concentrations. Researchers conducting rat inhalation studies believe that these effects most likely result from massive accumulation of small dust particles in the lung which overwhelm the natural lung clearance mechanism, known as "lung overload" phenomenon, rather than from a specific chemical effect of the dust particles in the lung.

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

carbon black (1333-86-4)	
LC50 fish 1	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

SB201L HI-FI Latent Print Powder, Silver/Black	
Persistence and degradability	Not established.
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

aluminium,powder,coated,dangerous (7429-90-5)	
Persistence and degradability	Biodegradability in soil: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
stearic acid (57-11-4)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	4 – 27 g O₂/g substance
BOD (% of ThOD)	0.49

12.3. Bioaccumulative potential

SB201L HI-FI Latent Print Powder, Silver/Black	
Bioaccumulative potential	Not established.

08/01/2024 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

carbon black (1333-86-4)		
Bioaccumulative potential	Not bioaccumulative.	
aluminium,powder,coated,dangerous (7429-90-5)		
Bioaccumulative potential	No test data of component(s) available.	
stearic acid (57-11-4)		
Partition coefficient n-octanol/water (Log Pow)	8.23 (Experimental value)	
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).	

12.4. Mobility in soil

carbon black (1333-86-4)		
Surface tension	Not applicable (solid)	
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.	
aluminium,powder,coated,dangerous (7429-90-5)		
Ecology - soil	Contains component(s) that adsorb(s) into the soil.	
stearic acid (57-11-4)		
Surface tension	29 mN/m (70 °C)	
Partition coefficient n-octanol/water (Log Koc)	4.71 (log Koc, Calculated value)	
Ecology - soil	Low potential for mobility in soil.	

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Proper Shipping Name (DOT) : Aluminum powder, coated

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Proper Shipping Name (IMDG) : ALUMINIUM POWDER, COATED

Air transport

Proper Shipping Name (IATA) : Aluminium powder, coated

SECTION 15: Regulatory information

15.1. US Federal regulations

SB201L HI-FI Latent Print Powder, Silver/Black

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

SB201L HI-FI Latent Print Powder, Silver/Black

Listed on the Canadian DSL (Domestic Substances List)

08/01/2024 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

SB201L HI-FI Latent Print Powder, Silver/Black

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

SB201L HI-FI Latent Print Powder, Silver/Black	
U.S California - Proposition 65 - Carcinogens List	Yes
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/01/2024

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources - heat, open flame, sparks. Avoid incompatible materials. Avoid dust creation and accumulation. Avoid inhalation and ingestion. Avoid contact with eyes. Wash thoroughly after handling.

Other information : This Safety Data Sheet has been established in accordance with the applicable European

Union legislation.

Full text of H-phrases:

	H228	Flammable solid
NFPA health hazard		: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard		: 1 - Materials that must be preheated before ignition can occur.
NFF	PA reactivity	: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.
Hazard Rating		
1114-		. 2 Maderate Hazard Tamperan, or miner injury may accur

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Personal protection : E

E - Safety glasses, Gloves, Dust respirator

SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.

08/01/2024 EN (English US) 7/7