DOC101



TECHNICAL INFORMATION

DUROCAST™ Impression Compound Catalog Nos. DOC1000, DOC101

INTRODUCTION

DUROCAST™ Impression Compound is a silicone casting material with extremely high sensitivity in recovering minute marks on various surfaces. This material is especially useful in recovering tool marks and marks or scratches on spent cartridges caused by the breech and extractor mechanisms.

DUROCAST™ consists of a putty-like base material and a catalyst. It is simple to use and is non-toxic when used according to directions.

DUROCASTTM is supplied as a complete kit (No. DOC1000) or it may be purchased in various refill sizes.



DOC1000 Kit and Components

TI02-38ENG-REV4







PROCEDURE

NOTE: Photograph impression with a scale before casting attempt.

- STEP 1. To properly mix the compound, begin with measuring out one level scoop full of base material, using the plastic scoop provided with the product.
- STEP 2. Flatten base material in the palm of your hand. Invert the scoop and press it into the compound.
- STEP 3. Squeeze a line of catalyst along the length of the scoop impression. Mix the two materials together, by hand, until a uniform color results. Do not exceed 30 seconds of mixing time



STEP 4

STEP 4. Press the compound into the impression to be cast immediately after mixing. One level scoop of base material will cover an area of approximately 1.5" x 3" (38mm x 51mm). Repeat the mixing procedure if a larger area must be covered. Allow 8-12 minutes for setup, and then remove the cast from the impression.

It is generally not necessary to use a release agent from most surfaces.

PRECAUTIONS

- Consult the appropriate Material Safety Data Sheets found on our website at www.sirchie.com/support.
- > Keep out of the hands of children. Not for human consumption.
- > Read through this entire instruction sheet prior to using the product.
- ➤ If stored at room temperature, this material has a shelf life of approximately 2 years. Do not store it in areas where it would be subjected to excessive heat such as the trunk of an automobile.

REFILL SUPPLIES CATALOG NO. DESCRIPTION

DOC1001	DUROCAST™	Impression Compound w/Catalyst, 1 oz. volume (28.3g)
DOC1002	DUROCAST™	Impression Compound w/Catalyst, 2.5 oz. volume (70.9g)
DOC101	DUROCAST™	Impression Compound w/Catalyst, 23.28 oz. (660g)
DOC330	DUROCAST™	Impression Compound w/Catalyst, 11.64 oz. (330g)
DOC100C	DUROCAST™	Catalyst, 5a



100 HUNTER PLACE, YOUNGSVILLE, NC 27596 USA 919-554-2244 • 800-356-7311

www.sirchie.com