

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/06/2015

Supersedes:02/02/2011

Version:

SECTION 1: Identification of the sub	stance/mixture and of the compar	ny/undertaking	
1.1. Product identifier			
Product form	: Mixture		
Product name.	: Invisible Metal Marking Ink		
Product code	: UV731		
	tance or mixture and uses advised agains	t	
Use of the substance/preparation	: Dyestuff		
1.3. Details of the supplier of the safety	data sheet		
SIRCHIE Finger Print Laboratories 100 Hunter Place 27596 Youngsville, NC - USA T 919-554-2244; 800-356-7311 - F 919-554-226 http://www.sirchie.com	6; 800-899-8181		
1.4. Emergency telephone number			
Emergency number	: 1.800.424.9300		
SECTION 2: Hazards identification			
2.1. Classification of the substance or m	ivture		
	inture		
Classification (GHS-US) Flam. Liq. 2	H225		
STOT SE 1	H370		
2.2. Label elements			
GHS-US labeling			
Hazard pictograms (GHS-US)	GHS02 GHS08		
Signal word (GHS-US)	: Danger		
Hazard statements (GHS-US)	: H225 - Highly flammable liquid and vapor H370 - Causes damage to organs (kidne		
Precautionary statements (GHS-US)	 P210 - Keep away from heat, hot surface P233 - Keep container tightly closed P240 - Ground/bond container and receiv P241 - Use explosion-proof electrical, ligl P242 - Use only non-sparking tools P243 - Take precautionary measures aga P260 - Do not breathe fume, vapors. P264 - Wash all exposed skin thoroughly P270 - Do no eat, drink or smoke when u P280 - Wear eye protection, protective gl P303+P361+P353 - IF ON SKIN (or hair) clothing. Rinse skin with water/shower P321 - Specific treatment (see informatio P370+P378 - In case of fire: Use CO2, or P403+P235 - Store in a well-ventilated pl P405 - Store locked up P501 - Dispose of contents/container to I 	ving equipment nting, ventilating equ ainst static discharge after handling. sing this product oves. : Remove/Take off i n on this label) ry chemical, foam, v ace. Keep cool	uipment. e mmediately all contaminated water spray for extinction.
2.3. Other hazards			
No additional information available			
2.4. Unknown acute toxicity (GHS US) No data available			
SECTION 3: Composition/informatio	n on ingredients		
3.1. Substances			
Not applicable			
3.2. Mixtures			
Name	Product identifier	%	Classification (GHS-US)

02/04/2013

1/6

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol	(CAS No.)67-56-1	96	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
Proprietary Formulation		2.77	Not classified
Leucophor BSB Special Liquid	(CAS No.)27344-06-5	1.23	Acute Tox. 1 (Dermal), H310
SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	: Never give anything by mouth to an advice (show the label where possib		If you feel unwell, seek medical
First-aid measures after inhalation	: Assure fresh air breathing. Allow the	victim to rest.	
First-aid measures after skin contact	: Remove affected clothing and wash by warm water rinse.	all exposed skin area	a with mild soap and water, followed
First-aid measures after eye contact	: Rinse immediately with plenty of wa persist.		
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiti	ng. Obtain emergenc	y medical attention.
4.2. Most important symptoms and e	· · ·		
Symptoms/injuries	: Not expected to present a significan	t hazard under anticip	pated conditions of normal use.
	ical attention and special treatment need	led	
No additional information available			
SECTION 5: Firefighting measures	5		
5.1. Extinguishing media			
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide.	Water spray. Sand.	
Insuitable extinguishing media	: Do not use a heavy water stream.		
5.2. Special hazards arising from the	substance or mixture		
Reactivity	: No reactivity hazard other than the e	effects described in su	ib-sections below.
5.3. Advice for firefighters			
Firefighting instructions	: Use water spray or fog for cooling e. chemical fire. Avoid (reject) fire-fight	ing water to enter env	vironment.
Protection during firefighting	: Do not enter fire area without proper	r protective equipmen	t, including respiratory protection.
SECTION 6: Accidental release me	easures		
6.1. Personal precautions, protective	equipment and emergency procedures		
6.1.1. For non-emergency personnel			
Emergency procedures	: Evacuate unnecessary personnel.		
6.1.2. For emergency responders			
Protective equipment	: Equip cleanup crew with proper prot	ection.	
Emergency procedures	: Ventilate area.		
6.2. Environmental precautions			
Prevent entry to sewers and public waters. No	otify authorities if liquid enters sewers or pu	blic waters.	
6.3. Methods and material for contain	ment and cleaning up		
Methods for cleaning up	: Soak up spills with inert solids, such spillage. Store away from other mate		ous earth as soon as possible. Colle
6.4. Reference to other sections			
See Heading 8. Exposure controls and perso	nal protection.		
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Precautions for safe handling	: Wash hands and other exposed are when leaving work. Provide good ve		-
7.2. Conditions for safe storage, inclu	uding any incompatibilities		
Storage conditions	: Keep only in the original container in closed when not in use.	a cool, well ventilate	d place away from : Keep container
ncompatible products	: Strong bases. strong acids.		
	: Sources of ignition. Direct sunlight.		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific end use(s)			
tional information availab	le		
ION 8: Exposure c	ontrols/personal protection		
Control parameters			
anol (67-56-1)			
ACGIH	ACGIH TWA (ppm)	200 ppm	
ACGIH	ACGIH STEL (ppm)	250 ppm	
	tional information availab ION 8: Exposure co Control parameters anol (67-56-1) ACGIH	tional information available ION 8: Exposure controls/personal protection Control parameters anol (67-56-1) ACGIH ACGIH TWA (ppm)	tional information available ION 8: Exposure controls/personal protection Control parameters anol (67-56-1) ACGIH ACGIH TWA (ppm) 200 ppm

8.2. **Exposure controls**

Personal protective equipment

: Avoid all unnecessary exposure. Gas mask. Gloves. Safety glasses.



Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Wear approved mask.
Other information	: When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	cher	nical properties
Physical state	:	Liquid
Appearance	:	Clear, colorless liquid.
Color	:	Colorless.
Odor	:	Alcohol odour.
Odor threshold	:	No data available
рН	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Self ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	No data available
Vapor pressure	:	No data available
Relative vapor density at 20 °C	:	No data available
Relative density	:	No data available
Solubility	:	Soluble in water.
Log Pow	:	No data available
Log Kow	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Explosive limits	:	No data available

Other information 9.2.

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. **Chemical stability**

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Not established.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4.	onditions to avoid	
Direct s	ght. Extremely high or low temperatures.	
10.5.	acompatible materials	
strong a	s. Strong bases.	
10.6.	azardous decomposition products	
fume. C	on monoxide. Carbon dioxide.	
SECT	SECTION 11: Toxicological information	
11.1.	formation on toxicological effects	
Acute to	ty : Not classified	

Acute toxicity	
Invisible Metal Marking Ink	
ATE (dermal)	300 mg/kg
methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg (1187-2769 mg/kg bodyweight; Rat; Rat)
LD50 dermal rabbit	15800 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	64000 ppm/4h (Rat)
Leucophor BSB Special Liquid (27344-06-5)	
LD50 oral rat	5000 mg/kg
LD50 dermal rat	4 mg/kg
ATE (oral)	5000 mg/kg
ATE (dermal)	4 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classifiedBased on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classifiedBased on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Causes damage to organs (kidneys, liver).
Specific target organ toxicity (repeated exposure)	: Not classifiedBased on available data, the classification criteria are not met
Aspiration hazard	: Not classifiedBased on available data, the classification criteria are not met

: Based on available data, the classification criteria are not met.

symptoms			

Potential Adverse human health effects and

|--|

12.1. Toxicity

methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; LETHAL)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; LETHAL)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)
12.2. Persistence and degradability	
Invisible Metal Marking Ink	
Persistence and degradability	Not established.
methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ² /g substance
Chemical oxygen demand (COD)	1.42 g O ² /g substance
ThOD	1.5 g O ² /g substance
BOD (% of ThOD)	0.40 - 0.73 % ThOD

Invisible Metal Marking Ink Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential	
Invisible Metal Marking Ink	
Bioaccumulative potential	Not established.
methanol (67-56-1)	
BCF fish 1	< 10 (Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other, Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
12.4. Mobility in soil	
methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
12.5. Other adverse effects	
Other information	: Avoid release to the environment.
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information	
In accordance with ADR / RID / ADNR / IMDG / IC	AO / IATA
14.1. UN number	
UN-No.(DOT)	: 1230
14.2. UN proper shipping name	
	: Methanol solution
	Toxic substance
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
	6.1 - Toxic substance
Packing group (DOT)	: II - Medium Danger
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport	
No additional information available	
Transport by sea	
No additional information available	
Air transport	
No additional information available	
SECTION 15: Regulatory information	
15.1. US Federal regulations	
Invisible Metal Marking Ink	
Listed on SARA Section 313 (Specific toxic chem	nical listings)
Listed on the United States TSCA (Toxic Substa	
15.2. International regulations	
CANADA	
No additional information available	
EU-Regulations	
No additional information available	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11

Full text of R-phrases: see section 16

15.2.2. **National regulations**

No additional information available

15.3. US State regulations

Invisible Metal Marking Ink()	
U.S California - Proposition 65 - Developmental Toxicity	Yes

SECTION 16: Other information	
Indication of changes	: Revision - See : *.
Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging. Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources - heat, open flame, sparks. Avoid incompatible materials. Avoid dust creation and accumulation. Avoid inhalation and ingestion. Avoid contact with eyes. Wash thoroughly after handling.
Other information	: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.
Full text of H-phrases: see section 16:	
Acute Tox. 1 (Dermal)	Acute toxicity (dermal) Category 1
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H310	Fatal in contact with skin
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs
NFPA health hazard NFPA fire hazard	 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given. 4 - Will rapidly or completely vaporize at normal pressure and temperature is readily dispersed in air and will hum.
	and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 4 Severe Hazard
Physical	: 1 Slight Hazard
Personal Protection	: G
SDS US (GHS HazCom 2012)	

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes