

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : UV7321 Fluorescent Invisible Coin Lacquer
 Product code : UV7321, UV732P

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Crime Scene Investigation

1.3. Supplier

SIRCHIE
 100 Hunter Place
 Youngsville, NC 27596 - USA
 T 919-554-2244; 800-356-7311 - F 919-554-2266; 800-899-8181
<http://www.sirchie.com>

1.4. Emergency telephone number

Emergency number : 1.800.424.9300 (USA) +1-703-527-3887 (INTL)
 CHEMTREC: 1.800.424.9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (inhalation:vapor) Category 3	H331	Toxic if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 1B	H350	May cause cancer
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
 H302 - Harmful if swallowed
 H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H331 - Toxic if inhaled
 H336 - May cause drowsiness or dizziness
 H340 - May cause genetic defects
 H350 - May cause cancer
 H361 - Suspected of damaging fertility or the unborn child
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P311 - Call a poison center or doctor.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
solvent naphtha(petroleum),light aliphatic	(CAS-No.) 64742-89-8	30	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
heptan-2-one	(CAS-No.) 110-43-0	23	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
butyl glycoether	(CAS-No.) 111-76-2	18	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
isobutanol	(CAS-No.) 78-83-1	12	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
toluene	(CAS-No.) 108-88-3	11	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
xylene, mixture of isomers	(CAS-No.) 1330-20-7	4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Invisible Green	(CAS-No.) Proprietary	< 1	Not classified

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
ethylbenzene	(CAS-No.) 100-41-4	0.7	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

UV7321 Fluorescent Invisible Coin Lacquer	
No additional information available	
butyl glycoether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
isobutanol (78-83-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	50 ppm
ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
xylene, mixture of isomers (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
heptan-2-one (110-43-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	50 ppm
toluene (108-88-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	20 ppm
Invisible Green (Proprietary)	
No additional information available	
solvent naphtha(petroleum),light aliphatic (64742-89-8)	
No additional information available	

8.2. Appropriate engineering controls

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gas mask. Gloves. Safety glasses.

Hand protection:

Wear protective gloves.

Eye protection:

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical goggles or safety glasses

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Pale yellow or light brown oily liquid.
Color	: Yellow
Odor	: Aromatic odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Sparks.

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Toxic if inhaled.

ATE US (oral)	1941.356 mg/kg body weight
ATE US (vapors)	9.303 mg/l/4h

butyl glycolether (111-76-2)

LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 Inhalation - Rat [ppm]	450-486,Rat; Weight of evidence

isobutanol (78-83-1)

LD50 oral rat	> 2830 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 18.18 mg/l air (6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 Inhalation - Rat	17.8 mg/l/4h (Rat; Literature study)
LC50 Inhalation - Rat [ppm]	4000 ppm/4h (Rat; Literature study)

xylene, mixture of isomers (1330-20-7)

LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
---------------	----------------------------------------------------------------------------------------------------------------------------------------

heptan-2-one (110-43-0)

LD50 oral rat	1600 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

toluene (108-88-3)

LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral (one dose), 7 day(s))
LD50 dermal rabbit	> 5000 mg/kg body weight (Other, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

butyl glycolether (111-76-2)

IARC group	3 - Not classifiable
------------	----------------------

ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

isobutanol (78-83-1)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

toluene (108-88-3)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

ethylbenzene (100-41-4)	
Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.

toluene (108-88-3)	
Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

isobutanol (78-83-1)	
LC50 fish 1	1430 mg/l (96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	1100 mg/l (ASTM, 48 h, Daphnia pulex, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	1799 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)

xylene, mixture of isomers (1330-20-7)	
LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
ErC50 (algae)	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

heptan-2-one (110-43-0)	
LC50 fish 1	131 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	> 90.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, GLP)

toluene (108-88-3)	
LC50 fish 1	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value)

12.2. Persistence and degradability

UV7321 Fluorescent Invisible Coin Lacquer	
Persistence and degradability	Not established.

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31
isobutanol (78-83-1)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 (20 days)
xylene, mixture of isomers (1330-20-7)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
heptan-2-one (110-43-0)	
Persistence and degradability	Readily biodegradable in water.
BOD (% of ThOD)	0.44
toluene (108-88-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

12.3. Bioaccumulative potential

UV7321 Fluorescent Invisible Coin Lacquer	
Bioaccumulative potential	Not established.
butyl glycolether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
isobutanol (78-83-1)	
Partition coefficient n-octanol/water (Log Pow)	1 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 – 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Partition coefficient n-octanol/water (Log Pow)	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
xylene, mixture of isomers (1330-20-7)	
BCF fish 1	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
heptan-2-one (110-43-0)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
toluene (108-88-3)	
BCF fish 1	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

toluene (108-88-3)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

butyl glycoether (111-76-2)	
Surface tension	0.027 N/m (25 °C)

isobutanol (78-83-1)	
Surface tension	69.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)
Partition coefficient n-octanol/water (Log Koc)	0.47 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Partition coefficient n-octanol/water (Log Koc)	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value

xylene, mixture of isomers (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

heptan-2-one (110-43-0)	
Surface tension	0.0591 N/m (21.6 °C, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Koc)	1.45 (log Koc, EU Method C.19, Experimental value)
Ecology - soil	Highly mobile in soil.

toluene (108-88-3)	
Surface tension	27.73 N/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint related material (FLAMMABLE LIQUID), 3, II
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint related material
FLAMMABLE LIQUID
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 3 - Flammable liquid



UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

UV7321 Fluorescent Invisible Coin Lacquer

Subject to reporting requirements of United States SARA Section 313
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

UV7321 Fluorescent Invisible Coin Lacquer

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging. Keep in tightly closed container. Keep cool and dry. Avoid all ignition sources - heat, open flame, sparks. Avoid incompatible materials. Avoid dust creation and accumulation. Avoid inhalation and ingestion. Avoid contact with eyes. Wash thoroughly after handling.

Other information : This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

UV7321 Fluorescent Invisible Coin Lacquer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Hazard Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal protection

: G

G - Safety glasses, Gloves, Vapor respirator

SDS US (GHS HazCom 2012)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes.